11) Center Drills / Centering Tools

 D_2 l ℓ_2 Dc Ds

Spiral Pointed Taps | Spiral Fluted Taps | Spiral Fluted Taps (for through hole) (for through hole)

Taps Hand 7

Taps

(10)

11-65

JO-CSQM

Joint- Countersinks 90°, Drilling Machine Use




Specification Cutting Speed depending on Materials

Stainless steels ステンレス鋼 5~10

Cast irons 10~25 (m/min)

■The JO-CSQM is a countersink joint tool for chamfering with a drilling machine.



Segment: 5C

Size D₂ × θ	Code	Dc (mm)	Ds (mm)	L (mm)	ℓ (mm)	ℓ ₂ (mm)	H (mm)	No. of flutes	Adaptable holder Shank dia.	TYPE	MSRP
16 × 90°	JCS016QM9	3.2	10	37.5	20	27.5	8	5	14	1	¥ 3,600
$20 \times 90^{\circ}$	JCS020QM9	4	12	43.5	24	32.5	10	5	16	1	¥ 4.070



JO-HOLDER


Holders for Joint Tools, for 150mm and for 200mm


YAMAWA **YAMAWA**

Specification



A holder exclusively for the Joint Tools. After installing into the Joint tool, we offer long types of 150 mm and 200 mm including the tool length.





Segment: 5A

Size	Code	Ds (mm)	L (mm)	ℓ (mm)	H (mm)	Applicable cutting edge shank dia.	TYPE	MSRP
14 × 150	JH1014M	14	122.5	86	12	10	1	¥ 8,780 [□]
16 × 150	JH1216M	16	117.5	80	14	12	1	¥ 8,740 [□]
20 × 150	JH1620M	20	115.5	74	17	16	1	¥ 9,180 [□]
14 × 200	JH1014N	14	172.5	136	12	10	1	¥ 10,100 [□]
16 × 200	JH1216N	16	167.5	130	14	12	1	¥ 9,980 [□]
20 × 200	JH1620N	20	165.5	124	17	16	1	¥ 11,200 [□]

