

lk l ls Ds K

Spiral Fluted Taps | Spiral Fluted Taps (for through hole)

Spiral

Taps

Hand T

(6)

(10)





Z-PRO

Coated Spiral Fluted Taps for Parallel Pipe Threads

Specification







Tapping Speeds depending on Materials















Product Features

- •New shape is adopted. Proper tool projection length is secured, achieving a good chip ejection efficiency.
- •Good internal thread surface and long tool life are achieved by the adoption of the unique cutting edge shape and special coating.

Tapping Data

Tapping conditions [AUSP Rp 1/4-19]

Workpiece Materials	SUS304
Tapping Speed	5m/min
Machine	Machining center
Holder	Fixed
Tapping Fluid	Water soluble cutting fluid









· Compatible with tapping of a wide range of work materials AUSP Rp Standard tapping conditions

Workpied	Standard Tapping Speed (m/min)			
Stainless Steels	SUS304	~ 3		
Alloy Steels	SCM/SCr	5~15		
High Carbon Steels	S45C~	5~15		
Medium Carbon Steels	S25C~S45C	5~15		
Low Carbon Steels	~S20C/SS400	5~15		
Aluminum Alloy Casting/ Zinc Alloy Casting	AC/ADC/ZDC	5~15		



JIS

Spiral Pointed Taps | Spiral Fluted Taps | Spiral Fluted Taps (for through hole) (for through hole) (Tor blind hole)

Hand Taps

Carbide Taps


4

Roll Taps

6

Special Thread Taps
Simple Inspection Tools

Precision Machinery/ | Nedical Surgical Instruments |



Segment: 1G

Size	Code	Chamfer	Basic major dia (mm)	L (mm)	l (mm)	ℓs _(mm)	Ds (mm)	K (mm)	ℓk (mm)	No. of flutes	TYPE	MSRP
For Pipe Threads												
Rp 1/8-28	SJRP020FET	C (2.5P)	9.728	90	15	46	8	6	9	3	1	¥ 5,320
Rp 1/4-19	SJRP040FET	C (2.5P)	13.157	100	19	51	11	9	12	3	1	¥ 7,910
Rp 3/8-19	SJRP060FET	C (2.5P)	16.662	100	21	51	14	11	14	3	1	¥ 12,500
Rp 1/2-14	SJRP080FET	C (2.5P)	20.955	125	26	64	18	14	17	4	1	¥ 19,700
Rp 3/4-14	SJRP120FET	C (2.5P)	26.441	140	28	71	23	17	20	4	1	¥ 32,600
Rp 1 -11	SJRP160FET	C (2.5P)	33.249	160	33	82	26	21	24	4	1	¥ 58,400