2 Spiral Fluted Tap Series for through hole

lk ls Ds

Spiral Fluted Taps
(for blind hole)

Spiral Pointed Taps (for through hole)

Hand Taps

Special Thread Taps
Simple Inspection Tools

(10)

F-SL



Spiral Fluted Taps for High Speed Tapping, Through Hole Use (with LH Spiral Flutes)

Specification











Tapping Speeds depending on Materials






F-SL, spiral fluted tap, through hole use (with LH spiral flutes) is applicable for such high speed tapping as 15m/min to 25m/min. Under low tapping speed, chip shape and chip ejection may become poor and cause tapping troubles.







Segment: 1S

Size	Class	Code	Chamfer	L (mm)	ℓ (mm)	ℓn _(mm)	ℓ s _(mm)	Ds (mm)	K (mm)	ℓk (mm)	No. of flutes	TYPE
For Metric Threads												
$M3 \times 0.5$	ISO2X	LD3.0GBNEV	5P	56	9	18	34	3.5	2.7	6	3	1
$M4 \times 0.7$	ISO2X	LD4.0IBNEV	5P	63	13	21	38	4.5	3.4	6	3	1
$M5 \times 0.8$	ISO2X	LD5.0KBNEV	5P	70	14	25	39	6	4.9	8	3	1
M6 × 1	ISO2X	LY6.0MBNEV	5.5P	80	15	30	45	6	4.9	8	3	2
$M8 \times 1.25$	ISO2X	LY8.0NBNEV	5.5P	90	19	35	48	8	6.2	9	3	2
$M10 \times 1.5$	ISO2X	LY010OBNEV	5.5P	100	23	39	53	10	8	11	3	2
$M10 \times 1.25$	ISO2X	LY010NBNEV	5.5P	100	19	39	53	10	8	11	3	2
$M12 \times 1.75$	ISO2X	LY012PBNEV	5.5P	110	26	45	56	12	9	12	3	2
$M12 \times 1.75$	ISO2X	LG012PBNEV	5.5P	110	26	-	56	9	7	10	3	3
$M12 \times 1.5$	ISO2X	LY012OBNEV	5.5P	110	23	45	56	12	9	12	3	2
$M12 \times 1.5$	ISO2X	LM012OBNEV	5.5P	100	21	-	51	9	7	10	3	3
$M12 \times 1.25$	ISO2X	LY012NBNEV	5.5P	110	19	45	56	12	9	12	3	2
$M12 \times 1.25$	ISO2X	LM012NBNEV	5.5P	100	21	-	51	9	7	10	3	3