

٤k l ls K Ds

Spiral Pointed Taps | Spiral Fluted Taps | Spiral Fluted Taps (for through hale) | (for blind hale)

(10)

DIN

LO-SP OX G



Low Spiral Fluted Taps for Parallel Pipe Threads, Oxidized

Specification








Tapping Speeds depending on Materials

<u>5~10</u>

■Spiral flutes with low helix can break down chips and can eject them smoothly. Suitable for thermal refined high carbon steels and alloy tool steels. Effective in horizontal tapping.



Segment: 1H

| Size | Class | Code | Chamfer | L (mm) | ℓ (mm) | ℓs (mm) | Ds (mm) | K (mm) | ℓk (mm) | No. of flutes | TYPE |
|---------------|-------|-------------|---------|-----------|-----------|------------|------------|-----------|------------|---------------|------|
| For G Threads | | | | | | | | | | | |
| G 1/8-28 | - | SVG0020NEXH | 3.5P | 90 | 19 | 46 | 7 | 5.5 | 8 | 3 | 1 |
| G 1/4-19 | - | SVG0040NEXH | 3.5P | 100 | 21 | 51 | 11 | 9 | 12 | 3 | 1 |
| G 3/8-19 | - | SVG0060NEXH | 3.5P | 100 | 21 | 51 | 12 | 9 | 12 | 3 | 1 |
| G 1/2-14 | - | SVG0080NEXH | 3.5P | 125 | 24 | 64 | 16 | 12 | 15 | 4 | 1 |
| G 3/4-14 | - | SVG0120NEXH | 3.5P | 140 | 27 | 71 | 20 | 16 | 19 | 4 | 1 |
| G 1 -11 | - | SVG0160NEXH | 3.5P | 160 | 29 | 82 | 25 | 20 | 23 | 4 | 1 |

