Overall length	Thread length	Position on basic dia.	Shank dia.	Size of square	Length of square
L	l	lg	Ds	K	ℓk

■The SP-S-PT is a spiral flute tapered pipe

tap and is used for thread tapping when it is necessary to shorten the fitting length with a product whose main purpose is the tightness of the threaded portion when connecting pipe



Spiral Fluted Taps | Spiral Fluted Taps (for through hole) | (for blind hole) |

Spiral Pointed Taps (for through hole)

Hand Taps

4

Carbide Taps Roll Taps

(6)

Special Thread Taps Simple Inspection Tools

Thread Mills

Thread Mills

Center Drills Centering Tools

(10)

Surgical Instruments

SP-S-PT



Spiral Fluted Taps for Taper Pipe Threads Short (lg) Type

Specification









Tapping Speeds depending on Materials




 ℓ_k



5

TYPE:2



parts etc.



Segment: 1G

TYPE: 1

 ℓ_{g}

Size	Class	Code	Chamfer	Basic major dia (mm)	L (mm)	ℓ (mm)	ℓg (mm)	Ds (mm)	K (mm)	ℓk (mm)	No. of flutes	TYPE	ı	MSRP
For Pipe Threads														
PT 1/16-28	П	SSPT01K	2.5P	7.723	55	16.5	10.5	8	6	9	3	1	¥	4,880 *
PT 1/8-28	I	SSPT02K	2.5P	9.728	55	16.5	10.5	8	6	9	3	2	¥	4,880
PT 1/4-19	п	SSPT04-	2.5P	13.157	62	19.5	12.5	11	9	12	3	2	¥	7,000
PT 3/8-19	п	SSPT06-	2.5P	16.662	65	21	14	14	11	14	3	2	¥	11,600
PT 1/2-14	п	SSPT08Q	2.5P	20.955	80	27	17	18	14	17	4	2	¥	19,000
PT 3/4-14	п	SSPT12Q	2.5P	26.441	85	29	19	23	17	20	4	2	¥	30,100
PT 1 -11	п	SSPT16U	2.5P	33.249	95	35	22	26	21	24	4	2	¥	55,500
PT 1 1/4-11	I	SSPT20U	2.5P	41.910	105	37.5	24.5	32	26	30	4	2	¥	83,800 *
PT 1 1/2-11	п	SSPT24U	2.5P	47.803	110	38.5	25.5	38	29	32	4	2	¥	118,000 *
PT 2 -11	I	SSPT32U	2.5P	59.614	120	42.5	27.5	46	35	38	4	2	¥ ·	191,000 *